
STANDALONE LINE

TOMRA T70™ Single

Recycling has a place in any space





TOMRA T70 Single/ENG/11.2024

MEASUREMENTS*

Dimensions [W x D x H]	813 mm x 1040 mm x 1690 mm
Infeed height	1194 mm
Adjustment range for height	+125 mm
Footprint	0.9 sqm
Weight [1]	275 kg [1]

STANDARD CONFIGURATION*

Machine type	Standalone reverse vending machine
Bin unload direction	Free-standing, front, or rear unload (Available in wall-mounted version)
Number of cabinets & bins	1 cabinet, 1 bin
Compactors *	PET crusher/ Can crusher/Mix crusher (cans, PET bottles), Glass crusher or Drop for glass bottles
Colors	RAL 7042 [possible to wrap machine for a custom look]
User interface	**Display:** 10,4'' touch display, video and sound capabilities, user guidance on machine screen **Printer:** Thermal printer

* Compactor selection may depend on the selected type of power supply on the machine (1ph/3ph).

RECOGNITION

Recognition technology	TOMRA Flow Technology™ (360° instant recognition, shape recognition, full container detection, barcode recognition, metal detection)
Speed capability [2]	Up to 45 containers per minute [2]

STORAGE CAPACITY*

Accepted containers	Up to 3 types of non-refillable containers: plastic bottles, cans and glass bottles
Storage capacity per bin [3]	**PET bottles:** Up to 1100 (compacted) [3] **Cans:** Up to 3200 (compacted) [3] **Glass bottles:** Up to 300
Container sizes (min/max size)	**Bottles:** 50-130 mm x 85-380 mm (D x H) **Cans:** 50-100 mm x 80-200 mm (D x H)

ENVIRONMENTAL

Humidity	Maximum 90% relative humidity, non-condensing
Temperature	+10°C to +40°C / +50°F to 104°F (For indoor or protected installation only)
Noise emission (in store)	**Glass bottles (glass crusher):** Lw = 92.5 dBA / Lp,d@1m = 75,5 dBA* (*All values ± 4dB). Measurements were performed based on ISO 9614-2 **PET bottles (compactor):** Lw = 79.3 dBA / Lp,d@1m = 62,3 dBA* (*All values ± 4dB). Measurements were performed based on ISO 9614-2 Aluminum cans (compactor): Lw = 78.7 dBA / Lp,d@1m = 61,7 dBA* (*All values ± 4dB). Measurements were performed based on ISO 9614-2

ELECTRICAL

Power consumption	Idle 61 W – Max. 2 kW
Mains *	400 V 3 ph 50 Hz, 16 A fuse / 208 V 3 ph 60 Hz, 20 A fuse, C-characteristics (dedicated grounded mains supply) 230 V 1 ph 50 H, 13-16 A fuse, C-characteristics (dedicated grounded mains)

* Depending on compactor selection

CONNECTIVITY

External IT interface	LAN (Ethernet TCP/IP), POS compatible
Digital tools	Fully compatible with TOMRA's portfolio of digital products and APIs

* May vary in different countries due to variations in beverage container materials, shapes and sizes.
[1] May vary according to packaging.
[2] Performance data may vary across markets, deposit regulations and system requirements.
[3] Capacities will vary with object mix, type and system configuration.

TOMRA

Get in the Loop at **tomra.com/reverse-vending**

ISO 9001 + 14001 Certified
Certificate no. 900031

TOMRA CERTIFICATION
TOMRA SYSTEMS ASA has implemented and maintains a Quality and Environmental Management System which fulfils Nemko's provisions for Management System Certification and the requirements of standards NS-EN ISO 9001:2015 and NS-EN ISO 14001:2015, with the scope described by the organization on 2018-05-29. The certification covers the development and delivery of automated systems for recycling.

LEGAL COMPLIANCE
The CE mark on this product confirms compliance with the following European Directives:
2006/42/EU, Community Legislation on Machinery.
2014/30/EU, Electromagnetic Compatibility (EMC).
2011/65/EU, Restrictions of Hazardous Substance (RoHS).
2012/19/EU, Waste Electrical and Electronic Equipment (WEEE).

We reserve the right to make changes to specifications without prior notice. While every effort has been made to ensure all information contained in this document is accurate, TOMRA assumes no liability for any errors, inaccuracies or omissions that may occur. All products and offers are subject to country availability. Please consider the environment before printing.